

## **DENSOPROOF 2000**

### **DESCRIPTION**

Densoproof 2000 is a flexible, self-adhesive, elastomeric membrane. This product is ideally suited for quick and effective waterproofing of concrete and timber decks with a good UV protection once over coated with a waterbased acrylic topcoat (Denso Acrylic Topcoat). Densoproof 2000 can also be used in the following applications:

- *Counter flashing.*
- *Ridge capping.*
- *Pipe dressing.*
- *Gutter sealing.*
- *Flat roof repairs.*
- *Valley linings.*
- *Roof sheet laps.*
- *Covering drive screws*
- *Counter flashing for torch applied membranes.*

### **COMPOSITION**

The membrane consists of an inert polyester fabric laminated to a pressure sensitive, reinforced, modified bitumen compound. The rolls are interleaved with a disposable release film.

### **SAFETY**

Normal hygiene procedures. Wash hands thoroughly with soap and water or a proprietary hand-cleaner prior to eating or smoking. Launder contaminated clothing, gloves, etc.

### **STORAGE**

Store in original containers in a cool dry place. Maximum recommended shelf life : 6 months.

**DENSOPROOF 2000 (cont.)**

TYPICAL PROPERTIES	TEST METHOD	DATA
<b>Adhesion</b> <ul style="list-style-type: none"><li>- To Primed Steel @23°C</li><li>- To Self @23°C</li></ul>	ASTM D1000 ASTM D1000	2.5N/mm 2.0N/mm
<b>Resistance to Acids, Alkalis &amp; Salts</b>		Excellent
<b>Temperature Range</b> <ul style="list-style-type: none"><li>- For application</li><li>- For Service</li></ul>		+15°C to 45°C +5°C to 65°C
<b>Length</b>		15m
<b>Width</b>		850mm
<b>Core Size</b>		76mm I.D
<b>Thickness</b> <ul style="list-style-type: none"><li>- Fabric Backing</li><li>- Adhesive</li><li>- Total</li></ul>	ASTM D1000	300µm 1200µm 1500µm
<b>Weight</b>		1.5Kg/m <sup>2</sup>
<b>Recommended Primer</b>		Denso Bitumen Primer D

**Important**

Winn & Coales / Denso SA (Pty) Ltd pursue a policy to develop and continually improve all of our products and therefore the information given in this data sheet is intended as a general guide and does not constitute a warranty of specification. However, our sales personnel are committed to assist the user in establishing the suitability of the product for its intended purpose and additional specific information is available on request.

Denso SA (Pty) Ltd operate a Quality Management System registered to ISO 9001:2008.