



DENSO SS HI-TACK PRIMER

DESCRIPTION Denso SS Hi-Tack Primer is a tacky adhesive primer for use with Denso petrolatum tapes. The primer is used on structural steel members where additional adhesive qualities are required. Denso SS Hi-Tack Primer is a component of the Denso Steelcoat System.

COMPOSITION Denso SS Hi-Tack Primer is a solvent based solution of saturated petroleum hydrocarbons blended with polymeric adhesion promoters.

SAFETY Denso SS Hi-Tack Primer is flammable and should not be applied in the vicinity of naked flames or sources of ignition.

Avoid contact with the skin and the inhalation of vapours.
Always ensure adequate ventilation is provided.

Normal hygiene procedures. Wash hands thoroughly with soap and water or a proprietary hand-cleaner prior to eating or smoking. Launder contaminated clothing, gloves, etc.

STORAGE Store in original containers in a cool, dry place away from any sources of ignition. Recommended shelf life: 12 months

TYPICAL PROPERTIES	DATA
Specific Gravity	0.85
Solids Content	70% w/w
Flash Point	32°C minimum
Covering Capacity	5m ² /lt
Wet Film Thickness	200µm
Dry Film Thickness	140µm
Drying Time	60 minutes (approx)
Temperature Range For Application For Service	0°C to 50°C 65°C maximum

Important

Winn & Coales / Denso SA (Pty) Ltd pursue a policy to develop and continually improve all of our products and therefore the information given in this data sheet is intended as a general guide and does not constitute a warranty of specification. However, our sales personnel are committed to assist the user in establishing the suitability of the product for its intended purpose and additional specific information is available on request.

Denso SA (Pty) Ltd operate a Quality Management System registered to ISO 9001:2008.

Head Office / Factory: 120 Malacca Road, Red Hill, Durban. P.O.Box 201259, Durban North, 4016, South Africa
Tel: +27 (031) 569 4319 Fax: +27 (031) 569 4328 Email: bid@denso.co.za Website: www.denso.co.za