

DENSO MARINE PILING TAPE

DESCRIPTION A cold applied petrolatum tape specially formulated for application under water or to wet surfaces. When applied spirally with sufficient tension it will displace water and develop a water resistant bond to metal surfaces. For the protection of Jetty Piles and other marine structures and any wet or submerged pipework. It provides the primary corrosion protection in Denso Seashield systems for jetty pile protection.

COMPOSITION Non-woven synthetic fibre fabric impregnated and coated with a neutral compound based on saturated petroleum hydrocarbons (Petrolatum), inert siliceous fillers, water displacing agents, wide spectrum biocides and a clear polyethylene backing. It is supplied in rolls in a range of widths.

SAFETY Normal hygiene procedures. Wash hands thoroughly with soap and water or a proprietary hand-cleaner prior to eating or smoking. Launder contaminated clothing, gloves, etc.

STORAGE Store in original containers in a cool, dry place. Recommended shelf life: 6 months
 Wrapped pipe should not be left exposed to direct sunlight for longer than fourteen (14) days.

TYPICAL PROPERTIES	TEST METHOD	DATA
Breaking Strength	ASTM D1000	200N/25mm minimum
Elongation at Break	ASTM D1000	10%
Resistance to Cathodic Disbonding	ASTM G8, 30day	Excellent
Temperature Range For Application For Service		5°C to 35°C maximum 45°C
Roll Length		10m
Roll Widths		50mm-300mm
Thickness	ASTM D1000	1.30mm average
Weight		1.62kg/m ² average
Recommended Primer		Denso S105 Paste

Note: Consult Denso SA (Pty) Ltd for information on outerwraps and covers for protection against damage.

Important

Winn & Coales / Denso SA (Pty) Ltd pursue a policy to develop and continually improve all of our products and therefore the information given in this data sheet is intended as a general guide and does not constitute a warranty of specification. However, our sales personnel are committed to assist the user in establishing the suitability of the product for its intended purpose and additional specific information is available on request.

Denso SA (Pty) Ltd operate a Quality Management System registered to ISO 9001:2008.

Head Office / Factory: 120 Malacca Road, Red Hill, Durban. P.O.Box 201259, Durban North, 4016, South Africa

Tel: +27 (031) 569 4319 Fax: +27 (031) 569 4328 Email: bid@denso.co.za Website: www.denso.co.za