

DENSO S105 PASTE

DESCRIPTION Denso S105 Paste is a soft brown petroleum based compound, containing moisture displacing and corrosion inhibiting additives, for all surfaces prior to the application of Denso Petrolatum Tapes.
Denso S105 Paste displays the following characteristics:

- *Non-drying / Non-hardening.*
- *Can be applied to moist surfaces.*
- *May be applied underwater by gloved hand, stiff bristle brush or roller.*

COMPOSITION Denso S105 Paste is a blend of saturated petroleum hydrocarbons, inert fillers and water displacing agents. It contains no volatile organic components.

SAFETY Avoid prolonged contact with the skin. Operators should wear oil-resistant gloves (PVC or NITRILE) or use a good proprietary barrier cream.

Normal hygiene procedures. Wash hands thoroughly with soap and water or a proprietary hand-cleaner prior to eating or smoking. Launder contaminated clothing, gloves, etc.

STORAGE Store in original containers in a cool, dry place.
Recommended shelf life: 12 months

TYPICAL PROPERTIES	DATA
Solids Content	>98%
Flash Point	180°C minimum
Specific Gravity	1.08
Specific Volume	925cc/kg
Coverage	2-5m ² /kg
Temperature Range <i>For Application</i> <i>For Service</i>	5°C to 40°C -25°C to 50°C

Surface Preparation	Surfaces should be free from mud, loose rust, scale, flaking coatings and marine growth.
----------------------------	--

Important

Winn & Coales / Denso SA (Pty) Ltd pursue a policy to develop and continually improve all of our products and therefore the information given in this data sheet is intended as a general guide and does not constitute a warranty of specification. However, our sales personnel are committed to assist the user in establishing the suitability of the product for its intended purpose and additional specific information is available on request.

Denso SA (Pty) Ltd operate a Quality Management System registered to ISO 9001:2008.

Head Office / Factory: 120 Malacca Road, Red Hill, Durban. P.O.Box 201259, Durban North, 4016, South Africa
Tel: +27 (031) 569 4319 Fax: +27 (031) 569 4328 Email: bid@denso.co.za Website: www.denso.co.za