

DENSO ALUMINIUM FOIL TAPE

DESCRIPTION	Denso Aluminium Foil Tape is used to seal the joints on air conditioning ducting and hot and cold insulation systems. <ul style="list-style-type: none"> • Specially formulated adhesive has excellent resistance to ageing and exhibits high peel and shear strengths. • Bonds well with most clean dry surfaces including steel, aluminium and most plastics.
COMPOSITION	A soft, pure aluminium foil, laminated to a clear pressure sensitive adhesive and interleaved with a disposable release film.
SAFTEY	Normal hygiene procedures. Wash hands thoroughly with soap and water or a proprietary hand-cleaner prior to eating or smoking. Launder contaminated clothing, gloves, etc.
STORAGE	Store in original containers in a cool, dry place. Maximum recommended shelf life: 6 months

TYPICAL PROPERTIES	DATA
Colour	Silver / Grey
Backing Type	Aluminium
Temperature Range <i>For Application</i> <i>For Service</i>	+5°C to +50°C -30°C to +105°C
Roll Length	50m (other lengths to order)
Width	48 & 96mm (or to order)
Core Size	78mm internal diameter
Thickness <i>Aluminium Backing</i> <i>Compound</i> <i>Total</i>	40 microns 25 microns 65 microns

Important

Winn & Coales / Denso SA (Pty) Ltd pursue a policy to develop and continually improve all of our products and therefore the information given in this data sheet is intended as a general guide and does not constitute a warranty of specification. However, our sales personnel are committed to assist the user in establishing the suitability of the product for its intended purpose and additional specific information is available on request.

Denso SA (Pty) Ltd operate a Quality Management System registered to ISO 9001:2008.