

DENSO ULTRAFLEX PSA 180 TAPE

DESCRIPTION Denso Ultraflex PSA 180 Tape is used as a protective outerwrap over Denso Petrolatum Tapes in buried applications. Not recommended as an outer wrap for exposed / above ground applications.

- Highly conformable.
- Impact and abrasion resistant for backfilling operations.
- This tape can be used in many other general applications.

COMPOSITION A modified polyethylene film, coated with a pressure sensitive adhesive.

SAFETY Normal hygiene procedures. Wash hands thoroughly with soap and water or a proprietary hand-cleaner prior to eating or smoking. Launder contaminated clothing, gloves, etc.

STORAGE Store in original containers in a cool, dry place. Recommended shelf life: 6 months
Wrapped pipe / fittings should not be left exposed to direct sunlight for longer than fourteen (14) days.

TYPICAL PROPERTIES	DATA
Carrier	Modified low density polyethylene
Adhesive	Water based Acrylic
Thickness	
• Backing film	125µ
• Adhesive	55µ
Tensile Strength	20 MPa
Elongation	>300%
Roll Length	30m
Roll Widths	48mm, 96mm, 150mm (or to order)
Colours	White, Yellow & Blue

Important

Winn & Coales / Denso SA (Pty) Ltd pursue a policy to develop and continually improve all of our products and therefore the information given in this data sheet is intended as a general guide and does not constitute a warranty of specification. However, our sales personnel are committed to assist the user in establishing the suitability of the product for its intended purpose and additional specific information is available on request.

Denso SA (Pty) Ltd operate a Quality Management System registered to ISO 9001:2008.

Head Office / Factory: 120 Malacca Road, Red Hill, Durban. P.O.Box 201259, Durban North, 4016, South Africa
Tel: +27 (031) 569 4319 Fax: +27 (031) 569 4328 Email: bid@denso.co.za Website: www.denso.co.za