

DENSO BUTYL EXTRUSIONS

DESCRIPTION

The tape is a butyl rubber based material with high surface tack and has the ability to re-seal on removal and re-application. The material has excellent water resistance, is non-hardening and retains its original form for pro-longed periods of time. The tape is soft, to facilitate ease of installation, but has good shear and yield strength. The tape is easily shaped by knife, resists flow and creep, has good resistance to both high and low temperatures and has outstanding resistance to weathering. The product does not stain, bleed into substrates (regardless of composition) nor corrode metals.

USES

Preformed butyl sealing tapes are used extensively as combination moisture barriers, adhesives, fillers and sealants in numerous applications in a wide range of industries including building, automotive and appliances.

ADVANTAGES

The tape offers the following advantages over caulks, cements and other liquid systems:

- Quick, clean, accurate installations
- Forms an immediate functional seal with no curing time or solvent evaporation.
- Requires no special mixing before installation.
- Requires no special installation equipment or skills.
- Has unlimited storage life

SAFETY

Normal hygiene procedures. Wash hands thoroughly with soap and water or a proprietary hand-cleaner prior to eating. Launder contaminated clothing, gloves, etc.

STORAGE

Store in original containers in a cool, dry place away from and sources of ignition. Unlimited Storage Life



LEADERS IN CORROSION PREVENTION AND SEALING TECHNOLOGY

TECHNICAL DATA SHEET

OVER 130 YEARS SERVICE TO INDUSTRY



ISO 9001:2008 Certified

Document Reference: TDS290B Rev: 01

TYPICAL PROPERTIES	DATA
Colour	Black
Solids Content	100%
Temperature Range <i>For Application</i> <i>For Service</i>	0°C to +60°C -10°C to +120°C
Strip Profile	Triangular (1.1m 20mm x 20mm x 20mm)
Tape Profile	3mm x 8mm x 15m 3mm x 25mm x 15m 3mm x 50mm x 15m

Important

Winn & Coales / Denso SA (Pty) Ltd pursue a policy to develop and continually improve all of our products and therefore the information given in this data sheet is intended as a general guide and does not constitute a warranty of specification. However,

Head Office / Factory: 120 Malacca Road, Red Hill, Durban. P.O.Box 201259, Durban North, 4016, South Africa

Tel: +27 (031) 569 4319 Fax: +27 (031) 569 4328 Email: bid@denso.co.za Website: www.denso.co.za



LEADERS IN CORROSION PREVENTION AND SEALING TECHNOLOGY

TECHNICAL DATA SHEET

OVER 130 YEARS SERVICE TO INDUSTRY



ISO 9001:2008 Certified

Document Reference: TDS290B Rev: 01

our sales personnel are committed to assist the user in establishing the suitability of the product for its intended purpose and additional specific information is available on request.

Denso SA (Pty) Ltd operate a Quality Management System registered to ISO 9001:2008.

Head Office / Factory: 120 Malacca Road, Red Hill, Durban. P.O.Box 201259, Durban North, 4016, South Africa
Tel: +27 (031) 569 4319 Fax: +27 (031) 569 4328 Email: bid@denso.co.za Website: www.denso.co.za

A MEMBER OF WINN & COALES INTERNATIONAL