



DENSO CLINGWRAP

DESCRIPTION Denso Clingwrap is a heavy duty polyethylene film used as a protective outerwrap over Denso Profiling Mastic / Denso Petrolatum Tape systems when applied to buried flanges, couplings and fittings.

- Highly conformable
- Excellent impact resistance
- Excellent resistance to water and moisture vapour

COMPOSITION A clear heavy duty polyethylene copolymer film. When wrapped upon itself under slight tension, binds the individual layers tightly to themselves, thus needing no external securing.

SAFETY Normal hygiene procedures. Wash hands thoroughly with soap and water or a proprietary hand-cleaner prior to eating or smoking. Launder contaminated clothing, gloves, etc.

STORAGE Store in original containers in a cool, dry place. Recommended shelf life: 6 months
Wrapped pipe / fittings should not be left exposed to direct sunlight for longer than fourteen (14) days.

TYPICAL PROPERTIES	DATA
Roll Length	250m
Roll Widths	100mm-150mm (or to order)
Film Thickness	40 μ

Important

Winn & Coales / Denso SA (Pty) Ltd pursue a policy to develop and continually improve all of our products and therefore the information given in this data sheet is intended as a general guide and does not constitute a warranty of specification. However, our sales personnel are committed to assist the user in establishing the suitability of the product for its intended purpose and additional specific information is available on request.

Denso SA (Pty) Ltd operate a Quality Management System registered to ISO 9001:2008.

Head Office / Factory: 120 Malacca Road, Red Hill, Durban. P.O.Box 201259, Durban North, 4016, South Africa

Tel: +27 (031) 569 4319 Fax: +27 (031) 569 4328 Email: bid@denso.co.za Website: www.denso.co.za