

Denso Butyl P16HT Primer

Primer for use with Denso Butyl Tapes

Composition

Denso Butyl P16HT Primer is comprised of adhesive in hydrocarbon solvent.

Uses

Denso Butyl P16HT Primer is used as primer for Denso Butyl tape systems.

Service temperature: -15 to +100°C

Application

See *Instructions for Use* for additional detail.

Storage conditions

Store Denso Butyl P16HT Primer in a cool (+0°C to +30°C), dry place, in original packaging.

Waste material

Please avoid or minimise waste wherever possible. Please do not discard waste material, including packaging, in the surrounding environment. Follow all relevant legislation for disposal

Typical properties

Colour	Black
Density	0.78 g/cm ³
Total solids	25%
Flash Point	-12°C
Consumption	4 m ² /l
Saponification value	<10 mg KOH/g
VOC	600 g/l
Shelf life	2 years

Important: Winn & Coales / Denso SA (Pty) Ltd pursue a policy to develop and continually improve all of our products and therefore the information given in this data sheet is intended as a general guide and does not constitute a warranty of specification. However, our sales personnel are committed to assist the user in establishing the suitability of the product for its intended purpose and additional specific information is available on request. Denso SA (Pty) Ltd operate a Quality Management System registered to ISO 9001.

Page 1 of 1

Revision date: 01/05/2021