

## Denso Butyl Profiling Mastic

A cold applied, self-supporting mastic

### Composition

Denso Butyl Profiling Mastic is based on butyl rubber.

### Uses

Denso Butyl Profiling Mastic is used for moulding around irregular profiles such as flanges, mechanical joints and valves to provide a contour suitable for wrapping with Denso Butyl Tapes.

### Characteristics

Denso Butyl Mastic is:

- suitable for service up to 100°C,
- permanently flexible,
- compatible with factory coatings of:
  - polyethylene,
  - polypropylene,
  - epoxy resin,
  - polyurethane, and
  - bitumen;
- easy to apply, and
- suitable for use in a wide range of climates.

### Surface Preparation

see *Instructions for Use* for additional detail

### Primer

Denso Butyl P16HT Primer

### Application

See *Instructions for use* for additional information.

### Availability

Denso Butyl Profiling Mastic is available in:  
20kg Boxes ,  
350mm x 50mm x 50mm x 65mm triangular strips.

### Storage conditions

Store in a cool and dry place in original packaging.

### Waste material

Please avoid or minimise waste wherever possible. Please do not discard waste material, including packaging, in the surrounding environment. Follow all relevant legislation for disposal.

### Typical properties

<b>Denso Butyl Profiling Mastic</b>	
Colour	Black
Density	1.5
Solids Content	100%

Important: Winn & Coales / Denso SA (Pty) Ltd pursue a policy to develop and continually improve all of our products and therefore the information given in this data sheet is intended as a general guide and does not constitute a warranty of specification. However, our sales personnel are committed to assist the user in establishing the suitability of the product for its intended purpose and additional specific information is available on request. Denso SA (Pty) Ltd operate a Quality Management System registered to ISO 9001.

Page 1 of 1

Revision date: 01/05/2021