

Densyl Tape

Conformable, cold-applied fabric tape for the corrosion protection of pipes

Composition

Durable synthetic fibre fabric impregnated and coated with a petrolatum compound.

Uses

Densyl Tape is used for the corrosion protection of buried or exposed pipes, valves, and fittings.

Service temperature: -20°C to +70°C

Characteristics

Densyl Tape is:

- resistant to water, water vapour and gases,
- resistant to mineral acids, alkali and salts,
- non-hardening, non-cracking, and
- conformable over a wide temperature range

Surface Preparation

See *Instructions for Use* for additional detail. Surfaces must be clean and dry. Remove all loose, rust, scale and flaking coatings by scraping, wire brushing or blast cleaning.

Apply Denso Paste, Denso S105 paste or Denso Priming Solution.

Application

See *Instructions for Use* for additional detail. Place the outer surface of the tape roll on the pipe. Wrap spirally around the pipe, taking care to overlap each layer by at least 55%. Smooth the compound with a gloved hand.

Application temperature: -5°C to +55°C

Availability

Densyl Tape is available in 10 metre rolls in widths from 50 mm to 900 mm.

Storage conditions

Store in a cool and dry place in original packaging.

Waste material

Please avoid or minimise waste wherever possible. Please do not discard waste material, including packaging, in the surrounding environment. Follow all relevant legislation for disposal.

Typical properties

Breaking Strength	200 N/50mm minimum	ASTM D1000
Elongation at Break	10%	ASTM D1000
Breakdown Voltage	16kV minimum per double layer	
Resistance to Cathodic Disbonding	<500 mm ²	ASTM G8 (30 days)
Total Thickness	1.15 mm	ASTM D1000
Weight	1.44 kg/m ²	

Important: Winn & Coales / Denso SA (Pty) Ltd pursue a policy to develop and continually improve all of our products and therefore the information given in this data sheet is intended as a general guide and does not constitute a warranty of specification. However, our sales personnel are committed to assist the user in establishing the suitability of the product for its intended purpose and additional specific information is available on request. Denso SA (Pty) Ltd operate a Quality Management System registered to ISO 9001.

Page 1 of 1

Revision date: 01/05/2021