

## Denso Grey Colour Tape

Grey-coloured cold applied tape for long-term corrosion protection

### Composition

Denso Grey Colourtape consists of a non-woven synthetic fibre fabric impregnated and coated with a stable grey pigmented petrolatum compound.

### Uses

Denso Grey Colour Tape is used for the protection of pipes, cables and fittings against corrosion.

Service temperature: -25°C to +60°C

### Characteristics

Denso Grey Colour Tape is:

- resistant to water, water vapour and gases,
- resistant to mineral acids, alkali and salts,
- U.V./Weather resistant,
- non-hardening, non-cracking, and
- conformable over a wide temperature range

### Application

See *Instructions for Use* for additional detail.

Remove all dirt, loose rust and flaking coating and mechanically clean to ISO 8501-1 St 2 surface cleanliness standard with steel wire brush.

No primer is required.

Application temperature: 0°C to +50°C

### Availability

Denso Grey Colour Tape is supplied in 10m rolls in widths 50, 75, 100 and 150 mm. Other sizes may be available on request.

### Storage conditions

Store in a cool and dry place in original packaging. Recommended shelf life is 5 years.

### Waste material

Please avoid or minimise waste wherever possible. Please do not discard waste material, including packaging, in the surrounding environment. Follow all relevant legislation for disposal.

### Typical properties

| Colour              | Grey                  | Visual     |
|---------------------|-----------------------|------------|
| Breaking Strength   | 4 N/mm                | ASTM D1000 |
| Elongation at Break | 10%                   | ASTM D1000 |
| Breakdown Voltage   | 8kV                   | BG CW 14   |
| Total Thickness     | 1.5 mm                | ASTM D1000 |
| Weight              | 1250 g/m <sup>2</sup> |            |

Important: Winn & Coales / Denso SA (Pty) Ltd pursue a policy to develop and continually improve all of our products and therefore the information given in this data sheet is intended as a general guide and does not constitute a warranty of specification. However, our sales personnel are committed to assist the user in establishing the suitability of the product for its intended purpose and additional specific information is available on request. Denso SA (Pty) Ltd operate a Quality Management System registered to ISO 9001.

Page 1 of 1

Revision date: 17/03/2025